



Technical Info.

Population Equivalent	6,000-10,000
Maximum flow per SMART unit:	80 l/s
Hydraulic loss at maximum flow:	50mm without weir box, approx. 250mm with weir box
Width of outlet weir (optional):	500mm
Head over weir at maximum flow:	170mm
Weight (kg)	i) Dry load - 6,300kg ii) In service - 14,200kg
Dimensions (mm)	4,692 - 4,962 (L), 2,600 (W), 2,440 (H)
Motor rating (kW)	2.2
Air sparge	1Nm ³ /min at 250mbar (intermittent)
Instrument options	Self cleaning dissolved oxygen meter

Terminations

Inlet:	300mm dia. flange to PN16
Outlet:	300mm dia. flange to PN16
Optional outlet weir box:	324mm O/D spigot pipe
Air sparge:	50mm flange to PN16



Materials

Item	Material	Coating
Tank	10mm carbon steel plate	ISO 12944/WIMES compliant
Rotating assembly	Carbon steel	Rilsan PA11
Rakes	304 Stainless steel	N/A
Mesh	Proprietary high voidage plastic mesh	N/A
Gearbox	Cast iron	Modified Epoxy
Cover	GRP	Gelcoat / Flowcoat

Technical Standards

Conforms to Supply of Machinery (Safety) Regulations 2008, Electrical Equipment (Safety) Regulations 2016, Electromagnetic Compatibility Regulations 2016, BS EN ISO 12100:2010, BS EN 60204-1:2018, BS EN 61000-6-2:2019 and BS EN 61000-6-4:2019

Contact Us:

London Office

Winchester House, 259-269 Old Marylebone Road, London, NW1 5RA.

Tel: +44 (0)20 7908 9500
enquires@bluewaterbio.com

